

APPLICATION  
FOR  
UNITED STATES PATENT

---

EXTENDED LENGTH  
LIGHT EMITTING DIODE

2004045007

## EXTENDED LENGTH LIGHT EMITTING DIODE

### CROSS REFERENCES TO CO-PENDING APPLICATIONS

[0001] None.

### BACKGROUND OF THE INVENTION

#### FIELD OF THE INVENTION

[0002] The present invention is for a light emitting diode, and in particular, provides for a extended length light emitting diode.

#### DESCRIPTION OF THE PRIOR ART

[0003] Light emitting diodes are incorporated into use for digit or pixel composition in scoreboards, message centers, graphic displays and the like whether indoors or outdoors. To improve viewability and to increase contrast, the main body of each LED extends individually through holes in a metal faceplate to form viewable alpha-numeric or graphic pixels or digits. The leads of multiple light emitting diodes (LEDs) are solder mounted to a printed circuit board. The relationship of the LEDs to the printed circuit board can take on several forms depending on if the display would be used inside or outside with respect to environmental sealing. Indoor use requires minimal sealing. However, if the display in which the LEDs are incorporated is for use in an outdoor environment, the LEDs can be flush mounted to a printed circuit board and a coating material can be applied to form a weatherproof seal to seal the base of the LED to the printed circuit board. Often a suitable seal with flush base mounting can be effected, but then the LED die, the region from which the light of an LED is emitted, may not extend a sufficient

distance through the display faceplate hole to be adequately viewed.

[0004] An alternative is provided whereby the LED body may be spaced from the printed circuit board by soldering the LED into place while spaced at a distance from the printed circuit board by varieties of spacing devices added between the LED and the printed circuit board or even more commonly by use of standoff tabs which are an integral part of the LED leads. Addition of spacers can include spacer devices which impart minimal stability of the LED. Often the spacers do not offer full support for the body of the LED nor do the spacers offer LED lead insulation or protection. Often spacers must be manually added, thus adding time and labor costs to the finished display product.

[0005] Such methods provide spacing and allow protrusion of the LED body through the faceplate, but application of coating material to the exposed leads of the LED extending between the body of the LED and the printed circuit board is difficult at best. Although spacing can be adequate with the preceding method, the bendable leads of the LEDs are subject to misalignment if not handled carefully and could make alignment with the holes in the faceplate difficult.

[0006] As the leads of the LEDs are electrically exposed to surrounding peripherally located cabinetry and support or other spacing members, or if gross misalignment of the LED to and through the faceplate holes occurs, and because the leads of the LEDs are subject to bending or misalignment, a potting compound can be made to flow about and to surround the LED leads thus sealing the LED base and the LED leads against environmental and other elements, whereby stability

of the LEDs is subsequently provided. However, such a process is time consuming and economically undesirable.

[0007] Clearly what is needed is an auto-insertable LED which avoids costly and timely spacing schemes having structure which can provide for adequate supported spacing of the main structure or body of an LED, including the LED die, from a printed circuit board while simultaneously providing for suitable projection of the LED die sufficiently through a faceplate and promoting of structure suitable for adequate sealing of the lower body portion of the LED and of the LED leads connected to the printed circuit board. The present invention provides for such as described herein.

## SUMMARY OF THE INVENTION

[0008] The general purpose of the present invention is to provide an extended length light emitting diode.

5 [0009] According to one embodiment of the present invention, there is provided an extended length light emitting diode having an extended LED body region substantially integral to and extending and making longer the length of the body of a light emitting diode. The extended length light emitting diode, which conforms to a cylindrically or other  
10 geometrically shaped LED body, extends over and about a portion of the LED electrical connection leads thereby insulating and supporting the covered portion of the connection leads. Such extension of the light emitting diode body terminates as a base which can align flush to a printed  
15 circuit board. The extended length of the light emitting diode allows for auto-insertion into a printed circuit board without an interceding spacer between the printed circuit board and extended length light emitting diode.

[0010] One significant aspect and feature of the present invention is an extended length light emitting diode which spaces an LED at a predetermined distance from a printed circuit board.

5 [0011] Another significant aspect and feature of the present invention is an extended length light emitting diode which spaces an LED die at a predetermined distance from an appropriately situated faceplate.

10 [0012] Still another significant aspect and feature of the present invention is an extended length light emitting diode which covers and electrically insulates a portion of LED leads from any adjacent metal support structures.

15 [0013] Yet another significant aspect and feature of the present invention is an extended length light emitting diode which supports and stabilizes an LED.

20 [0014] A further significant aspect and feature of the present invention, as illustrated in an alternative embodiment, is an add-on light emitting diode body extension region which can be aligned and attached to an existing unmounted LED to space the LED from a printed circuit board, as well as addressing the other significant aspects and features listed above.

25 [0015] A yet further significant aspect and feature of the present invention is an extended length light emitting diode of the first embodiment which is suited for printed circuit board auto-insertion.

30 [0016] A still further significant aspect and feature of the present invention is an extended length light emitting diode of the first embodiment which does not require the use of manually placed spacing devices.



## BRIEF DESCRIPTION OF THE DRAWINGS

[0018] Other objects of the present invention and many of the attendant advantages of the present invention will be readily appreciated as the same becomes better understood by reference to the following detailed description when considered in connection with the accompanying drawings, in which like reference numerals designate like parts throughout the figures thereof and wherein:

[0019] FIG. 1 illustrates an extended length light emitting diode, the present invention, having an extended LED body region substantially integral to and extending downwardly and adding to the length of the body of a light emitting diode;

[0020] FIG. 2 illustrates a cross section view of FIG. 1 along line 2-2 of FIG. 1;

[0021] FIG. 3 illustrates the embodiment of FIG. 2 flush mounted and soldered to a printed circuit board;

[0022] FIG. 4, an alternative embodiment, illustrates an LED body extension which in its structure is separate from the body of an LED and which can be aligned to or aligned to and attached to, such as by an adhesive, a lower planar base of an LED body to form a combined LED and LED body extension structure, and;

[0023] FIG. 5 illustrates a cross section view of FIG. 4 along line 5-5 of FIG. 4 where the LED body extension and the light emitting diode are mated in full combination.



## DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0024] FIG. 1 illustrates the present invention, an extended length light emitting diode 14, also referred to as LED 14, having an extended LED body region 10, shown substantially integral to and extending downwardly from a reference plane 16, shown in a dashed line, extending through the extended length light emitting diode 14, thereby adding to the length of the body 12 of the extended length light emitting diode 14. Reference plane 16, which shows the lower base limits of some commonly found LEDs, is included for purposes of illustration and clarity and is not part of the invention. The extended LED body region 10, also shown in FIG. 2, extends downwardly to cover and encompass an upper portion of LED electrical connection leads 18 and 20. The extended LED body region 10 terminates as a planar base 22 distanced from the lower ends of the LED electrical connection leads 18 and 20. The body 12 and the extended LED body region 10 are fashioned of a suitable plastic or other suitable material where one such material could include epoxy.

[0025] FIG. 2 illustrates a cross section view of FIG. 1 along line 2-2 of FIG. 1. Illustrated in particular is the extended LED body region 10 extending downwardly over and about the upper regions of the LED electrical connection leads 18 and 20 which lead to the internally located components of the extended length light emitting diode 14. The lower regions of the LED electrical connection leads 18 and 20 which are not covered by the extended LED body region 10 are available for placement through and connection to a printed circuit board as shown in FIG. 3. The planar base 22 is available for flush placement and mounting on the upper surface of a printed circuit board subsequent to which a coating material may be applied to seal around the base 22 of the extended length light emitting diode 14.

[0026] FIG. 3 illustrates the embodiment of FIG. 2 flush mounted and soldered to a printed circuit board 24 subsequent to auto-insertion. Coating material 26 is shown applied around and about the periphery of the planar base 22 to seal the lower region of the extended length light emitting diode 14 to the upper surface of the printed circuit board 24. The LED die 28, which is the area from which light is emitted, is shown placed as desired in a position well through a hole 30 in a faceplate 32 which is well suited for viewability. Flush mounting of the planar base 22 provided by the extended LED body region 10 to the printed circuit board 24 as well as providing for sealing processes provides for accurate placement and excellent supported stability of the body 12 of the extended length light emitting diode 14 with respect to the printed circuit board 24 and with respect to holes 30 in the faceplate 32. Auto-insertion of the extended length light emitting diode 14 is readily and easily accomplished by auto-insertion equipment and the time consuming manual placement of stand alone spacing devices is obviated.

[0027] FIG. 4, an alternative embodiment, illustrates an LED body extension 10a which in its structure is separate from the body 12a of a light emitting diode 14a and which can be aligned to or aligned to and attached to, such as by an adhesive, a lower planar base 16a of the body 12a to form a combined stabile structure consisting of the LED 14a and the attached LED body extension 10a, such as illustrated in FIG. 5. Such a combination allows a user to combine the LED body extension 10a with in-stock LEDs without having to produce a one-piece LED having an extended LED body region 10, such as previously described. The LED body extension 10a is appropriately shaped to conform to the horizontal cross section shape of an LED and includes an upper planar surface 19 and an opposing lower planar surface 22a. Geometrically configured and vertically aligned holes 34 and 36 extend vertically between the upper planar surface 19 and the lower planar surface 22a of the LED body extension 10a to accommodate engagement of the electrical connection leads 18 and 20 and to provide for insulation of the electrical connection leads 18 and 20. The body 12a and the LED body extension 10a are fashioned of a suitable plastic or other suitable material where one such material could include epoxy.

[0028] FIG. 5 illustrates a cross section view of FIG. 4 along line 5-5 of FIG. 4 where the LED body extension 10a and the light emitting diode 14a are mated in full combination. Illustrated in particular is the LED body extension 10a aligned over and about the upper regions of the LED electrical connection leads 18 and 20 which lead to the internally located components of the LED 14a. The lower regions of the LED electrical connection leads 18 and 20 which are not covered by the LED body extension 10a are available for placement through and connection to a printed circuit board. The mated LED planar base 16a of the light emitting diode 14a and upper planar surface 19 of the LED body extension 10a provides for stable planar surface to planar surface support of the light emitting diode 14a. The planar base 22a is available for flush placement and mounting on the upper surface of a printed circuit board subsequent to which a coating material may be applied to seal around the base 22a of the LED 14a.

1979年  
 1980年  
 1981年  
 1982年  
 1983年  
 1984年  
 1985年  
 1986年  
 1987年  
 1988年  
 1989年  
 1990年  
 1991年  
 1992年  
 1993年  
 1994年  
 1995年  
 1996年  
 1997年  
 1998年  
 1999年  
 2000年  
 2001年  
 2002年  
 2003年  
 2004年  
 2005年  
 2006年  
 2007年  
 2008年  
 2009年  
 2010年  
 2011年  
 2012年  
 2013年  
 2014年  
 2015年  
 2016年  
 2017年  
 2018年  
 2019年  
 2020年  
 2021年  
 2022年  
 2023年  
 2024年  
 2025年  
 2026年  
 2027年  
 2028年  
 2029年  
 2030年  
 2031年  
 2032年  
 2033年  
 2034年  
 2035年  
 2036年  
 2037年  
 2038年  
 2039年  
 2040年  
 2041年  
 2042年  
 2043年  
 2044年  
 2045年  
 2046年  
 2047年  
 2048年  
 2049年  
 2050年  
 2051年  
 2052年  
 2053年  
 2054年  
 2055年  
 2056年  
 2057年  
 2058年  
 2059年  
 2060年  
 2061年  
 2062年  
 2063年  
 2064年  
 2065年  
 2066年  
 2067年  
 2068年  
 2069年  
 2070年  
 2071年  
 2072年  
 2073年  
 2074年  
 2075年  
 2076年  
 2077年  
 2078年  
 2079年  
 2080年  
 2081年  
 2082年  
 2083年  
 2084年  
 2085年  
 2086年  
 2087年  
 2088年  
 2089年  
 2090年  
 2091年  
 2092年  
 2093年  
 2094年  
 2095年  
 2096年  
 2097年  
 2098年  
 2099年  
 2100年

[illegible]